



MATERIAL SAFETY DATA SHEET

PRODUCT NAME: DM-11

PRODUCT CODE: 0109

MANUFACTURED BY:	Acme Soap, Inc. 1206 Fulton Ave. San Antonio, TX 78201 (210)731-9800	Date Prepared 09/18/03 Revised: 11/14/2008
-------------------------	---	---

HMIS Rating: Health: 1 Flammability: 1 Reactivity: 1 Personal Protection: N/A

I. CHEMICAL IDENTIFICATION:

NAME: DM-11		
DESCRIPTION: Polish		
OTHER DESIGNATIONS:	MANUFACTURER:	EMERGENCY PHONE NUMBER:
	Acme Soap, Inc. 1206 Fulton Ave. San Antonio, TX 78201	(800)424-9300 CHEMTREC

II. HAZARDOUS INGREDIENTS

Ingredient	% Concentration	Worker Exposure Limits
Mineral Seal Oil	90	500 ppm

III. HEALTH HAZARD DATE

May cause headache, nausea, dizziness if used in a confined space.
Light irritant to skin and eyes.

Possible routes of entry are skin, eyes and ingestion.

Skin: Wash affected areas with soap and water.
Eyes: Causes burning and irritation. Flush eyes with large amounts of clear water for at least 15 minutes. If irritation persists, consult a physician, preferably an ophthalmologist.
Ingestion: May cause abdominal discomfort, nausea, vomiting and diarrhea. **DO NOT INDUCE VOMITING.** Obtain medical attention.
Never give anything by mouth to an unconscious person.
INHALATION: Remove victim to fresh air. If labored breathing persists, contact a physician.

IV. SPECIAL PROTECTION INFORMATION

PVC coated gloves, goggles and general ventilation should be adequate. Eye bath should be in near vicinity.

V. SPECIAL PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

Keep from freezing.

Avoid splash filling.

Avoid excessive heat and contact with strong oxidizing agents.

VI. SPILL OR LEAK PROCEDURES

Spilled product will cause floors and stairways to become extremely slippery. Contain spills immediately and avoid discharge to natural waters. Small spills may be flushed to sanitary sewer.

Contaminated product must be disposed of in accordance with Federal, State and local regulations.

VII. REACTIVITY DATA

Hazardous polymerization will not occur.

This product will react with strong oxidizers.

Hazardous by-products CO₂ when combusted.

VIII. FIRE AND EXPLOSION DATA

Flash Point 200 F closed cup.

Use CO₂ or dry chemical to extinguish.

Use self-contained breathing apparatus with a full face operated in pressure demand or other SCBA.

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

IX. PHYSICAL DATA

Appearance: Light colored liquid

Odor: Slight hydrocarbon

Boiling Point: 490°F.

Specific Gravity: 0.80 where water is 1.00.

Evaporation Rate: 0.05

Vapor Density: 5.3

Vapor Pressure: 1.0

NOTE:

The information provided on this Material Safety Data Sheet has been compiled from information obtained from the manufacturers of the raw material components of the product, as well as from laboratory tests on the finished product. There are no expressed or implied warranties to be derived from the information provided. The user assumes all risks in handling and must determine if this product is fit for its intended use.

The health hazards on this Material Safety Data Sheet apply to this product in its concentrated form (as supplied) and may differ significantly at use dilution. The signs and symptoms of overexposure apply only to negligence in handling or misuse of the concentrated product and not to the routine exposure to the diluted product under conditions of ordinary use.