



1206 FULTON AVE.
SAN ANTONIO, TX 78201
www.acmesoap.com

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: PTO-70

PRODUCT CODE: 0708

MANUFACTURED BY:

Acme Soap, Inc.
1206 Fulton Ave.
San Antonio, TX 78201
(210)731-9800

Date Prepared 01/05/02
Date Revised: 11/14/2008

HMIS Rating: Health: 1 Flammability: 0 Reactivity: 0 Personal Protection: A

I. CHEMICAL IDENTIFICATION:

NAME: PTO-70

DESCRIPTION: White Mineral Oil, NF

OTHER DESIGNATIONS:

MANUFACTURER:

EMERGENCY PHONE NUMBER:

Acme Soap, Inc.
1206 Fulton Ave.
San Antonio, TX 78201

(800)424-9300
CHEMTREC

II. HAZARDOUS INGREDIENTS

Ingredient

% Concentration

Worker Exposure Limits

There are no hazardous ingredients in this product.
A mix of liquid hydrocarbons refined from petroleum.

III. HEALTH HAZARD DATE

Possible routes of entry are skin, eyes and ingestion.

Skin: Wash affected areas soap and with clear water.

Eyes: Flush eyes with large amounts of clear water for at least 15 minutes. If irritation persists, consult a physician, preferably an ophthalmologist.

Ingestion: May cause abdominal discomfort. **DO NOT INDUCE VOMITING.** Obtain medical attention.

Never give anything by mouth to an unconscious person.

IV. SPECIAL PROTECTION INFORMATION

Wear chemical resistant gloves, goggles and general ventilation should be adequate.

V. SPECIAL PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

Avoid heat (150^o F. max.), flame and oxidizing agents.

VI. SPILL OR LEAK PROCEDURES

Spilled product will cause floors and stairways to become extremely slippery. Contain spills immediately and avoid discharge to natural waters. Small spills may be flushed to sanitary sewer.

Contaminated product must be disposed of in accordance with Federal, State and local regulations.

VII. REACTIVITY DATA

Hazardous polymerization will not occur.

Product is stable. This product is non-reactive.

#40 Oil is a fully refined white mineral oil meeting the Food and Drug Administration as per CFR 172.878 and CFR 178.3620(A).

CAS # 8042-47-5

VIII. FIRE AND EXPLOSION DATA

Flashpoint (method used: ASTM D-92) >120°C >250°F

Self-contained breathing apparatus is recommended for firefighters.

Water mist must be used with caution to prevent spread of flames.

IX. PHYSICAL DATA

Appearance: Viscous colorless liquid

Odor: None

pH: 7.0

Boiling Point: 450°F.

Specific Gravity: <1.00 where water is 1.00

Negligible solubility in water.

FREIGHT CLASSIFICATION: Petroleum Oil NOIBN

NOTE:

The information provided on this Material Safety Data Sheet has been compiled from information obtained from the manufacturers of the raw material components of the product, as well as from laboratory tests on the finished product. There are no expressed or implied warranties to be derived from the information provided. The user assumes all risks in handling and must determine if this product is fit for its intended use.

The health hazards on this Material Safety Data Sheet apply to this product in its concentrated form (as supplied) and may differ significantly at use dilution. The signs and symptoms of overexposure apply only to negligence in handling or misuse of the concentrated product and not to the routine exposure to the diluted product under conditions of ordinary use.